

Wall washer downlight



S01 Series



S201-01-9 9W
S201-01-12 12W



S202-01-15 15W
S202-01-20 20W



S203-01-25 25W
S203-01-30 30W



S204-01-35 35W
S204-01-40 40W

Applications:

Hotels, clubs, museums, shopping mall, offices, educational institutions etc.

Product Features:

1. Module structure, adapted to different LED light source and beam angles.
2. Different colors and anti-glare designs of reflectors for choice, realizing spot, flood or wallwasher lighting effect.
3. Patented structure design, die cast lamp body, simple and elegant.
4. UGR<15 accurate light distribution, pure light spot, multi-anti-glare technology.
5. control gears with non-flicker, smart control, etc.
6. IP20, IP44 for option.
7. Powers ranging from 9 W to 40W.
8. Lifespan up to 35,000 hours, 5 years warranty.

Structure and characteristics

- | | |
|--|--|
| <p>1 Light engine</p> <ul style="list-style-type: none"> - CREE, BRIDGELUX COB module - High lumen, high CRI, vivid & uniform lighting effect - Multiple beam angles for choice - High lumen output, accurate distribution, soft & comfortable lighting effect | <p>3 Front case</p> <ul style="list-style-type: none"> - high quality die-cast aluminum - Secondary optical design, accurate distribution, equal and comfort lighting effect - Fit to direct lighting or wallwashing applications |
| <p>2 Driver</p> <ul style="list-style-type: none"> - PF>0.8, optional dimming with 0-10V or TRIAC - According with LVD, EMC standard | |

Specific characteristics

 <p>Non-flicker driver</p>	 <p>Dimmable driver (optional)</p>	 <p>Series of products, multiple dimensions for choice</p>	 <p>Different colors for Anti-glare ring</p>
 <p>Suitable for wallwashing</p>	 <p>cut-off angle>30°</p>	 <p>UGR UGR<15</p>	





● Gray ● Black



Model	Dimension(mm)	Cut out(mm)	Power	Luminous	Packing(mm)
S201-01-9	Φ90x96	Φ75	9W	720lm	40pcs /CTN 522x460x230
S201-01-12	Φ90x96	Φ75	12W	960lm	40pcs /CTN 522x460x230
S202-01-15	Φ115x127	Φ100	15W	1200lm	18pcs /CTN 425x395x290
S202-01-20	Φ115x127	Φ100	20W	1600lm	18pcs /CTN 425x395x290
S203-01-25	Φ140x160	Φ125	25W	2000lm	18pcs /CTN 500x470x360
S203-01-30	Φ140x160	Φ125	30W	2400lm	18pcs /CTN 500x470x360
S204-01-35	Φ165x175	Φ150	35W	2800lm	12pcs /CTN 545x386x390
S204-01-40	Φ165x175	Φ150	40W	3200lm	12pcs /CTN 545x386x390

