



LED Wall light RT15

Features

- Cost-effective solid-state solution for general area applications, replacing high power luminaires.
- High Efficiency LED source to give maximum illuminations.
- Unique passive cooling system, uses an increased cooling surface area to reduce the operating temperature of LEDs and Driver.
- Built in surge protection.
- High light transmittance PC diffusers.
- Driver components from FIRST MOS (USA), MPS IC CHIP (USA), Rubycon Capacitor (JAPAN),

Applications

- Offices, Corridors, Residential applications etc.

Specifications

Model No.	S0223-RT-15
Type	Wall light
Light Source	LG 2835 SMD LED
Power	15W
Luminous efficacy	80LM/W
Luminous flux	1200LM
CCT	4000K (840)
Beam Angle	Wide
SDCM	<6
Dimming	No
Material	Aluminium, PC diffuser
Dimension	L300 x W140 x H145mm
Net Weight	1Kg
Certifications	CE, RoHS

Input Voltage	100-277VAC
Frequency	50-60Hz
Driver	Inbuilt
THD	<20%
Power factor	>0.9
Operating temperature	-20 ⁰ to 50 ⁰ C
CRI	>83
Life	35,000 Hours (L70)
T Cas Max (Tc)	55 Deg C
Fixture Colour	Black / Grey
IP Rating	IP65
Mounting	Surface mount
Warranty	3 years

Photometric data

