



Tri-proof batten light-4FT-24W

Features

- Energy efficient replacement for conventional fluorescent light fixtures.
- High efficiency 9th generation LED light source, 120-degree beam angle for maximum illumination.
- Unique aluminium heatsink passive cooling system, uses an increased cooling surface area to reduce the operating temperature of LEDs and Driver.
- Driver components from FIRST MOS (USA), MPS IC CHIP (USA), Rubycon Capacitor (JAPAN).
- Built in surge protection.
- Suitable for 24Hr usage per day.
- High light transmittance PC diffusers.
- Flicker free & Instant ON.
- RoHS Compliant.
- Mercury-free.

Applications

- Warehouses, Garages, Hotels, Offices, Museums, Residential applications.


Specifications

Model No.	S05320-24
Type	Light fixture
Light Source	2835 SMD LED
Power	24W
Power Factor	0.9
THD	<20%
Beam Angle	120°
CCT	4000K (840)
SDCM	<6
IP Rating	IP66
Material	Aluminium + PC
Lamp finish	White
Warranty	5 years
Equivalent lamp power	24W LED=2*35W T5 FL Tube fixture


Input Voltage	175-265VAC
Frequency	50-60Hz
Driver	Inbuilt
Luminous flux	3600LM
Luminous efficacy	150LM/W
Life	50000Hrs (L70)
CRI	>83
Dimming	No
T Cas Max (Tc)	60° C
Working Temperature	-25 to 45°C ¹
Dimension	L1200*W67*H65mm
Mounting	Surface mount / Wall mount / Hanging
Net weight	1150gm
Certifications	CE, RoHS, LM80, LM79 ²

@ All the above information at a testing condition:- Ta=25°C


Photometric Data




Luminous Intensity Distribution Diagram




Lumen maintenance



Life time



Dimensions



A= 67mm, B= 65mm, C=1200mm

Product Pictures



- 1 – Recommended to keep the ambient temperature in this limit while installing in closed spaces / fixtures
- 2 – Will be provided up on request